



furniture company


Item #: V60Y712 Assembly Instructions



For our most current instructions, to request missing, lost or broken parts, or for any other Customer Service issues, please visit our website at **www.walkeredison.com** or call us at 877-207-5906.




Hardware List




The hardware quantities listed above are required for proper assembly.


Some extra hardware may also have been included.




Carefully lay glass (1) upside down on a soft surface. Screw long rods (A) and short rods (B) into the appropriate metal plates of glass (1).




Slide cylinders (4) onto outside long rods (A). Slide cylinders (5) onto middle long rods (A). Slide decorative rings (D) onto long rods (A) and snap onto cylinders (4,5).




Carefully slide glass (3) into place using middle long rods (A) as guides. Slide decorative rings (D) onto middle long rods (A).




Slide cylinders (6) onto middle long rods (A). *Cylinders (6) will fit snuggly into the decorative rings placed in the previous step.* Slide decorative rings (D) onto middle long rods (A) and snap onto cylinders (6).




Carefully slide glass (3) into place using middle long rods (A) as guides. Slide decorative rings (D) onto middle long rods (A).




Slide cylinders (6) onto middle long rods (A). Cylinders (6) will fit snuggly into the decorative rings placed in the previous step. Slide decorative rings (D) onto middle long rods (A) and snap onto cylinders (6).






Screw cylinders (7) onto long rods (A). Cylinders (7) will fit snuggly into the decorative rings placed in the previous step.



Insert caps (E) into cylinders (7). Note that caps (E) may come pre-inserted into cylinders (7).



To attach cable management system (8) to the stand, place appropriate holes of cable management system (8) over short rods (B). Screw cap nuts (C) onto short rods (B) and tighten with wrench (F).

